

Leak Containment



Fastank bund for containment of fuel or chemical spills. Manufactured to ISO 9001 2008. Quality standard from (900gsm) rip stop acrylic and vinyl coated polyester fabric with aluminium wall supports. Registered Design No: 2104475.

Benefits:

- Simple assembly, no tools required
- Easy to transport, low weight and size
- Suitable for all climates
- Corrosion resistant
- Air inflation not required
- Adapts to uneven ground
- Easy to clean
- Supplied in an easy carry bag

Applications:

- Bunding of tanks and drums
- Plant and generator bunding
- Catches fuel and chemical spills or drips
- Portable decontamination pool for people and equipment
- Effluent, sewage, and waste liquid catchment
- Vehicle and equipment wash-down



Accessories: Ground mat

- Provides extra protection on rough or sharp ground
- Made from heavy duty vinyl coated reinforced fabric
- Can be used to provide an additional washable work area

Overflow control kit

- Automatically drains rainwater from underneath floating oil or debris
- Offers controlled overflow and emptying of bund
- Valve outlet for flow regulation
- Corrosion resistant

Polythene liner

- Made from virgin food grade polythene
- Prevents cross contamination
- Minimises cleaning of tank after use
- Protects tank from aggressive liquids and chemicals

CODE	SIZE	ASSEMBLED	PACKAGED	WEIGHT	CAPACITY
FASTANK BUND					
FTB0250	1 x 1m	1 x 1 x 0.25m	0.6 x 0.10 x 0.30m	5.2kg	250L
FTB0500	1 x 2m	1 x 2 x 0.25m	0.6 x 0.10 x 0.30m	7.5kg	500L
FTB1000	2 x 2m	2 x 2 x 0.25m	0.6 x 0.15 x 0.35m	11kg	1000L
FTB1750	2 x 3.5m	2 x 3.5 x 0.25m	0.6 x 0.15 x 0.35m	16kg	1750L
FTB4000	3.5 x 4.5m	3.5 x 4.5 x 0.25m	0.8 x 0.15 x 0.6m	28kg	4000L

Temporary Storage Tanks



FASTANK RAPIDE

For emergency containment and washdown. Manufactured to ISO 9001 2008. Quality standard from (900gsm) rip stop acrylic and vinyl coated polyester fabric. Structural aluminium frame and purpose designed joints. Stainless steel fittings. Temp Range -20°C to +80°C. UV Resistant.

Benefits:

- Simple assembly, no tools required
- Low packaged volume and weight
- Corrosion resistant
- Quick to set up
- Easy to clean
- Multi-purpose uses
- Can be hand carried

Available add-ons:

- Ground mat
- Hand pump
- Roof cover
- Polythene liner
- Decanting valve
- Pipe kit
- Pipe saddle, foot plates
- Anti-slip mat, support bars

Applications:

- Oil spill clean-up and decontamination pool
- Over-splash protection
- Containment of leaks
- Animal rescue enclosure
- Liquid storage
- Soiled sorbant storage
- Supplied in carry bag



Accessories: Ground mat - FTR0002

- Provides extra protection on rough or sharp ground
- Made from heavy duty vinyl coated reinforced fabric
- Can be used to provide an additional washable work area

Roof cover - FTR0004

- Reduces evaporation, rain ingress and contamination
- Can be reversed for use as a rainwater catcher

Pipe saddle - FTR0006

- 75mm or 50mm
- Simple to attach - no tools
- Safely pump over the tank

Polythene liner - FTR0008

- Made from virgin food grade polythene
- Prevents cross contamination
- Minimises cleaning of tank after use

Hand pump - FTR0010

- Output 110L/min
- Attaches easily to tank
- Includes 2m of suction hose and 5m of 38mm diameter outlet hose

CODE	ASSEMBLED	PACKAGED	WEIGHT	CAPACITY
FASTANK RAPIDE				
FTR0001	1.72 x 1.67 x 0.6m	1.75 x 0.23 x 0.18m	15kg	1500L